

S5138
Ethernet IO Modules
8 Channels Universal AI
16 Channels DO, 6 Channels DI



SHJ

Sales: Michael@shjelectronic.com

Support: support@shjelectronic.com

S5138 is a high quality and low cost analog data acquisition module with 8 universal analog inputs. Each input can be 0-5V,0-10V,0-20mA,thermistor,dry contact, open-collector input,6 isolated digital input and 16 channels isolated open-collector digital output. The digital input can be dry contact, wet contact and open-collector, each input also can be 32-bit counter.S5138 has RS485 and rj45 two type interface,rs485 support standard Modbus RTU protocol and RJ45 support Modbus Tcpip protocol.It can easy integrate with PLC and labview with standard Modbus/Modbus Tcpip protocol

Highlights:

- Surge-protected analog inputs with 12-bit resolution and 100k sample speed
- Input can be any combination of 0-5V,4-20mA,0-10V,NTC 10K thermistor, open-collector and dry contact
- The channel number is configurable, can be set up from 1 channel through 8 channels, for analog input and set up from 1 to 6 for digital input, improve sample rate for small count input
- Isolated digital inputs can be configured as counter input, total 32 bits,1000Hz
- Total 16 channels isolated open-collector digital output
- Standard ModBus TCPIP protocol,easy work with PLC
- Standard ModBus protocol allows for up to 254 unique devices on one RS485 network
- A lot of spare FLASH can be used to store user's parameters
- Can update your firmware via ISP through RS485 network, can provide any hex file to help you finish some logic control
- DIN support available


Application:

- ✓ Remote data acquisition
- ✓ Process monitoring
- ✓ Industrial process control
- ✓ Energy management
- ✓ Supervisory control
- ✓ Security systems
- ✓ Laboratory automation
- ✓ Building automation
- ✓ Product testing
- ✓ Direct digital control


Technical data:


Analog Input Resolution-----	12-bit
Analog Input Channel Number-----	8
Analog Input range-----	0-5V,0-10v,0-20mA, thermistor, dry contact,open-collector
Analog Input Protection-----	Lightning,static
Analog Input Accuracy-----	±0.1%
Analog Input Zero drift-----	±3uV/°C
Analog Input Sample Rate-----	60 sample/second(8 channels),900 sample/second(1 channel)
Digital Input Channel Number-----	6
Digital Input Range-----	+4V~+36V
Digital Input Signal-----	wet contact, dry contact, open-collector
Digital Input Counter Frequency-----	100Hz@6channels;1000Hz@1channel
Digital Input Counter Length-----	32-bit
Output channel number-----	16
Output signal-----	open-collector
Output current-----	maximum 40mA
Output BUS-----	Ethernet/RS485
RS232/RS485 protocol-----	MODBUS/RTU
Ethernet protocol-----	MODBUS/TCP/IP
Output Protection-----	Lightning,static
Power input-----	15~24V(AC/DC)
Power consumption-----	<0.6W
Ambient temperature:	
Operation-----	-20~85°C(-4~185°F)
Storage-----	-40~125°C(-40~257°F)
Ambient humidity-----	10%~90%RH
Material,enclosure-----	Flame proof plastic
Enclosure rating-----	IP31
Colour-----	White/Black
Size-----	115*90*43 mm

Wiring diagram and description:






Top view figure



Communication wiring diagram

Thermistor
0-5V
0-10V
4-20mA
SENSOR

Analog inputs wiring diagram**Dry contact wiring diagram**



Inputs

Each analog input can be jumper-configured in 1 of 4 ways:

- ◊ 0-5V signal
- ◊ 0-10V
- ◊ 0-20mA
- ◊ Dry contact, thermistor, open-collector. thermistor default is 10K NTC, but can custom according

to your sensor type

All digital inputs can be jumper-configured in 1 of 2 ways:

- ❖ Wet contact input
- ❖ Dry contact, open-collector input

PINs and LEDs

Power supply

24VAC: power supply positive input, has reverse protection, accept AC and DC input

- : Power supply negative input

RS485 Port

B: Connect to B of RS485

A: Connect to A of RS485

R: Connect to GND for RS485

Ethernet port

Connect to local Ethernet network through RJ45 cable

Inputs

Analog:

A1 ~ A8: Analog input 1 through 8

AGND: common for analog input 1 through 8,also use for analog output

Digital:

DVCC: Power source input for digital input 1 through 6,wet contact input available

D1 ~ D6: Digital input channel 1 through 6

DGND: common for digital input 1 through 6, available in dry input mode

Outputs

Digital:

O1~O16: Digital output channel 1 through 16

OGND: common GND for digital output 1 through 16

Leds

BEAT: Will flash when system is working

Comm: Will flash when RS485 serial port communication

Modbus register list:

Note: * means default value

Address	Bytes	Value range		Description	Property
		Min	Max		
0-3	4	1	4294967295	Serial number,unique for each product	R
4-5	2	100	65535	Firmware version number	R
6	1	1	254	Device address,default is 254*	R/W
7	2	5138	5138	Product model	R

8	1	1	255	Hardware version	R																		
9	2	12	1152	Baudrate setting <table border="1"> <thead> <tr> <th>Value</th> <th>Baudrate</th> </tr> </thead> <tbody> <tr><td>12</td><td>1200</td></tr> <tr><td>24</td><td>2400</td></tr> <tr><td>48</td><td>4800</td></tr> <tr><td>96</td><td>9600</td></tr> <tr><td>192*</td><td>19200*</td></tr> <tr><td>384</td><td>38400</td></tr> <tr><td>576</td><td>57600</td></tr> <tr><td>1152</td><td>115200</td></tr> </tbody> </table> For example:write 96 to register 9 to set the baudrate 9600.	Value	Baudrate	12	1200	24	2400	48	4800	96	9600	192*	19200*	384	38400	576	57600	1152	115200	R
Value	Baudrate																						
12	1200																						
24	2400																						
48	4800																						
96	9600																						
192*	19200*																						
384	38400																						
576	57600																						
1152	115200																						
10-99	-	-	-	Reserved	-																		
100-107	2	0	4095	Analog reading for channel input 1 through 8,the units decided by register 119 through 126	R																		
108	1	0	255	Status for digital input channel 1 through 6, 0 = contact active,1 = contact inactive.Bit0 correspond to channel 1,bit1 correspond to channel 2 etc.	R																		
109	2	0	65535	Open-collector output,0 = active,1 = inactive.Bit0 correspond to output 1,bit1 correspond to channel 2 etc.	R/W																		
110	-	-	-	Reserved	-																		
111~117	-	-	-	Reserved	-																		
118	1	0	255	Enable/disable the corresponding channel,0 = disable,1* = enable.Bit0 correspond to channel 1 and Bit7 correspond to channel 8.For example,enable channel 1,2 and disable channel 3 through 8,write 0x03 to register 118.	R/W																		
119-126	1	0	8	Channel 1 through 8 units setting.0* = raw AD sample reading,1 = 0~5V(real value = the current reading / 100,for example, the current reading is 288,the real voltage is $288/100 = 2.88V$),2 = 0~10V(real value = current reading / 100),3 = 4~20mA(real value = the current reading / 100),4 = 0~100%,5 = ON/OFF,6 = OFF/ON,7 = 10K thermistor, celsius(real value = current reading / 10),8 = 10K thermistor,Fahrenheit(real value = current reading / 10).	R/W																		
127-134	1	0	100	Channel 1 through 8 Filter factor,0 = no filter,10* is default.	R/W																		
135,137, 139 ...	2	0	4095	In calibration mode, channel 1 through 8 sample data as input 0 volts	R/W																		

136,138 140...	2	0	4095	In calibration mode, channel 1 through 8 sample data as input is full scale	R/W
151	-	-	-	Reserved	-
152	-	-	-	Reserved	-
153,155 ...	-	-	-	Reserved	-
154,156 ...	-	-	-	Reserved	-
167~174	2	0	1000	Analog input 1 through 8 in temperature units, use calibrate temperature by adjust the offset	R/W
175	2	0	65535	High word for digital input1 counter	R/W
176	2	0	65535	Low word for digital input1 counter, value of counter = (175) *65536 + (176)	R/W
177	2	0	65535	High word for digital input2 counter	R/W
178	2	0	65535	Low word for digital input2 counter, value of counter = (177) *65536 + (178)	R/W
179	2	0	65535	High word for digital input3 counter	R/W
180	2	0	65535	Low word for digital input3 counter, value of counter = (179) *65536 + (180)	R/W
181	2	0	65535	High word for digital input4 counter	R/W
182	2	0	65535	Low word for digital input4 counter, value of counter = (181) *65536 + (182)	R/W
183	2	0	65535	High word for digital input5 counter	R/W
184	2	0	65535	Low word for digital input5 counter, value of counter = (183) *65536 + (184)	R/W
185	2	0	65535	High word for digital input6 counter	R/W
186	2	0	65535	Low word for digital input6 counter, value of counter = (185) *65536 + (186)	R/W
187	2	0	65535	High word for digital input7 counter	R/W
188	2	0	65535	Low word for digital input7 counter, value of counter = (187) *65536 + (188)	R/W
189	2	0	65535	High word for digital input8 counter	R/W
190	2	0	65535	Low word for digital input8 counter, value of counter = (189) *65536 + (190)	R/W
191	2	1	30000	Filter time for counter input, the units is 10us and the default is 200us	R/W

192	1	0	255	Disable/enable input,0 = disable and 1 = enable.Bit0 correspond to input1, Bit1 correspond to input 2 and so on.	R/W
193	1	0	1	Input status selection.0 = ON/OFF,1 = OFF/ON, default is ON/OFF	R/W
194	1	0	1	Digital input counter will increase at rising edge or falling edge.0 = rising edge,1 = falling edge, default is rising edge	R/W
195	1	1	100	Respond delay for serial communication, the units is ms and default is 10ms	R/W
196	1	0	1	Default is 0, write 1 enable store counter when power off.	R/W
197	1	0	1	1, rs485 has highest priority;0 ethernet has highest priority	R/W
198	2	0	65535	Unit is second, setting period no communication, reset the module	R/W
199	-	-	-	reserved	-
200-203	1	0	255	Device local IP address, default is 192.168.0.X	R/W
204-207	1	0	255	Gate way address, default I is 192.168.0.1	R/W
208-211	1	0	255	Subnet address, default is 255.25.255.0	R/W
212-217	1	0	255	MAC address	R/W
218	2	0	65535	Port number, default is 502. Write this register also save value of register 200 to 218.	R/W

Default Settings:

Device ID: 254, 255 is broadcast address

Data Format: 1 start bit, 8 data bit, 1 stop bit, none parity

Baudrate: 19200

There are a INIT jumper inside the board,short INIT then power on S5138,parameters will go to default settings.